


Tire Inflation Cages • Cajas para inflado de llantas • Cages de sécurité pour gonflement de pneus

Mandatory for any shop working with tubeless and multi-piece rims. Made from heavy-gauge steel tubing welded to a steel base. Guards against blown lock rings and rims. Follow OSHA regulation 29-CFR Part 1910.177. Read safety label on cage. Designed to meet OSHA regulation requirements for Medium, Heavy-Duty Truck, OTR, Tractor, and Super Singles. Ken-Tool offers sizes and designs for all your needs. For additional safety labels, instructions or OSHA rim matching charts, call Ken-Tool customer service.



Work safely.
Always use an inflation cage when inflating tires.
Follow OSHA regulation 29-CFR Part 1910.177 whenever changing tires.

Passenger and Light Truck Cage

Jaula para camión liviano y para pasajeros

Cabine passager et véhicule utilitaire léger

A must for run-flat, low-profile, and other tires that are difficult to seat.



Model	EDP No.	Height A**	Width B	Base	Weight
T103	36003	30" 76 cm	16" 41 cm	21-1/2" x 22" 55 cm x 56 cm	80 lbs 36.2 kg

NEW

Portable Wide Base Cage

Caja con base amplia portátil

Cage portative à base large

Especially designed for wide base tires, this portable inflation cage will hold super singles, and super wide radial tires. Fits comparable tires up to: 445/50R 22.5.




Model	EDP No.	Height A**	Width B	Base	Weight
T101A	36007	43-1/2" 111 cm	20-1/2" 52 cm	7" closed x 27" 18 cm closed x 69 cm	72 lbs 32.6 kg

Portable 2-Bar Cage

Caja de dos barras portátil • Cage portative à deux barres

U.S. Patented No. D270,216

Model	EDP No.	Height A**	Width B	Base	Weight
T101	36001	41" 104 cm	16" 41 cm	7" closed x 21-1/2" 18 cm closed x 55 cm	60 lbs 27.2 kg



3-Bar Cage

Caja de 3 barras

Cage à 3 barres

Model	EDP No.	Height A**	Width B	Base	Weight
T106	36006	43-1/2" 111 cm	20-1/2" 52 cm	26" x 22" 66 cm x 56 cm	134 lbs 60.7 kg



4-Bar Cage

Caja de 4 barras

Cage à 4 barres

Model	EDP No.	Height A**	Width B	Base	Weight
T102	36002	43-1/2" 111 cm	20-1/2" 52 cm	31-1/2" x 26" 80 cm x 66 cm	146 lbs 66.2 kg

5-Bar Cage

Caja de 5 barras

Cage à 5 barres



Model	EDP No.	Height A**	Width B	Base	Weight
T105	36005	43-1/2" 111 cm	20-1/2" 52 cm	41" x 26" 104 cm x 66 cm	182 lbs 82.5 kg

3-Bar Cage (OTR)

Caja de 3 barras (de carretera)

Cage à 3 barres (pneus tout terrain)



Model	EDP No.	Height A**	Width B	Base	Weight
T104	36004	65" 165 cm	24" 61 cm	30" x 27" 76 cm x 69 cm	158 lbs 72.6 kg

** Height A refers to the approximate height to the inside bend of the cage.

WARNING: Tire changing can be dangerous, and should be done only by trained personnel using proper tools and equipment as directed by Federal OSHA Standard No. 29 CFR Part 1910.177. Tires may explode during inflation causing injury to operator or bystander. Wear safety goggles. Keep all parts of body outside cage. Use extension hose, clip-on chuck, and remote valve. See supervisor for safety procedures.

WARNING: Do not alter cage in any way. Cage must be freestanding and at least three feet from other objects. Discard cage if bent, cracked, or otherwise damaged. Always wear safety goggles.

Truck Tire Changing Stand

Soporte para cambio de llantas de camiones

Support de démontage pour pneus de camions



Stand handles wheels or open rims 16.5" to 24". Double-slide adjustment with locking device prevents twisting so it stays aligned with the wheel or rim. Stand is the ideal height for driving off beads or demounting tires. It must be used to be appreciated.

Model	EDP No.	Weight
T115	36015	21 lbs (9.5 kg)