

**26400/  
26401**

*AW-80T (26400 and 26401) Stubby  
Impact Wrench*



**26402/  
26403**

*AW-80J (26402 and 26403) Micro  
Stubby Impact Wrench*



**26404**

*AW-130P Impact Wrench*



**26406**

*AW-140P Heavy Duty Impact Wrench*



**26405**

*AW-130PL Impact Wrench*



**26407**

*AW-140PL Heavy Duty Impact Wrench*



**26408**

*AW-220P 3/4" Drive Heavy Duty  
Impact Wrench*



**26409**

*AW-322GL 1" Drive Heavy Duty  
Impact Wrench*



**UNIQUE AND INNOVATIVE DESIGNS FEATURING  
ULTRA-COMFORTABLE ERGONOMICS.**

The high quality build provides a longer life of the tool.

**AIR BOSS MINI STUBBY  
IMPACT WRENCH**

*Air Pressure: 90psi  
Air Inlet & Minimum Air Hose: 1/4"*

AW-80T (26400 and 26401) Mini Stubby Impact Wrench featuring twin hammer clutch type. 9,000 RPM Free Speed.

Part Number	Drive	Torque Range (ft-lb)	Max Torque	Overall Length	Net Weight (lbs)	Air Consumption (Gal/Min)
26400	3/8"	25-225	428	3.74"	2.62	79.25
26401	1/2"	25-225	450	3.74"	2.62	79.25



**AIR BOSS MICRO STUBBY  
IMPACT WRENCH**

*Air Pressure: 90psi  
Air Inlet & Minimum Air Hose: 1/4"*

AW-80J (26402 and 26403) Micro Stubby Impact Wrench featuring jumbo hammer clutch type. 9,000 RPM Free Speed.

Part Number	Drive	Torque Range (ft-lb)	Max Torque	Overall Length	Net Weight (lbs)	Air Consumption (Gal/Min)
26402	3/8"	21-190	375	3.3"	2.44	79.25
26403	1/2"	25-225	406	3.42"	2.46	79.25



**AIR BOSS IMPACT WRENCH  
26404**

*Air Pressure: 90psi  
Air Inlet: 1/4"  
Minimum Air Hose: 3/8"*

AW-130P 1/2" drive with twin hammer clutch.

Part Number	Free Speed (RPM)	Torque Range (ft-lb)	Max Torque	Overall Length	Net Weight (lbs)	Air Consumption (Gal/Min)
26404	6,200	50 - 552	780	6.45"	4.9	179.63



**AIR BOSS IMPACT WRENCH  
26405**

*Air Pressure: 90psi  
Air Inlet: 1/4"  
Minimum Air Hose: 3/8"*

AW-130PL 1/2" drive with twin hammer clutch.

Part Number	Free Speed (RPM)	Torque Range (ft-lb)	Max Torque	Overall Length	Net Weight (lbs)	Air Consumption (Gal/Min)
26405	6,200	50 - 552	780	7.64"	5.1	179.63



**AIR BOSS HEAVY DUTY IMPACT  
WRENCH 26406**

*Air Pressure: 90psi  
Air Inlet: 1/4"  
Minimum Air Hose: 3/8"*

AW-140P 1/2" drive with twin hammer clutch.

Part Number	Free Speed (RPM)	Torque Range (ft-lb)	Max Torque	Overall Length	Net Weight (lbs)	Air Consumption (Gal/Min)
26406	6,700	50 - 596	1253	6.53"	4.9	179.63



**AIR BOSS HEAVY DUTY  
IMPACT WRENCH 26407**

*Air Pressure: 90psi  
Air Inlet: 1/4"  
Minimum Air Hose: 3/8"*

AW-140PL 1/2" drive with twin hammer clutch.

Part Number	Free Speed (RPM)	Torque Range (ft-lb)	Max Torque	Overall Length	Net Weight (lbs)	Air Consumption (Gal/Min)
26407	6,700	50 - 596	1253	7.75"	5	179.63



**AIR BOSS HEAVY DUTY IMPACT  
WRENCH 26408**

*Air Pressure: 90psi  
Air Inlet: 3/8" & Minimum Air Hose: 3/8"*

AW-220P 3/4" Drive with twin hammer clutch.

Part Number	Free Speed (RPM)	Torque Range (ft-lb)	Max Torque	Overall Length	Net Weight (lbs)	Air Consumption (Gal/Min)
26408	4,800	349-929	1328	8.66"	9.9	132.08



**AIR BOSS HEAVY DUTY IMPACT  
WRENCH 26409**

*Air Pressure: 90psi  
Air Inlet & Minimum Air Hose: 1/2"*

AW-322GL 1" Drive with swing hammer clutch.

Part Number	Free Speed (RPM)	Torque Range (ft-lb)	Max Torque	Overall Length	Net Weight (lbs)	Air Consumption (Gal/Min)
26409	4,200	668-1459	1852	20.87"	22	158.5



For product registration information, go to <https://www.kentool.com/air-tool-registration/>

For product warranty/repair information, go to <https://www.kentool.com/air-tool-warranty-repair-form/>

