



WHEREVER TIRES ARE CHANGED™


AIR HOSES

PREMIUM REINFORCED HYBRID AIR HOSES

Advanced Hybrid Hose features the Strength of reinforced PVC with the superior flexibility of rubber!

Item No.	Length	Male Fittings	Max Pressure	Inside Diameter
26100	100 ft (30m)	1/4" Brass	300 psi	3/8" (9.2mm)
26065	65 ft (20m)	1/4" Brass	300 psi	3/8" (9.2mm)
26032	32 ft (10m)	1/4" Brass	300 psi	3/8" (9.2mm)

STAYS FLEXIBLE IN THE COLD,
DOESN'T KINK IN THE HEAT



WITH 1/4" BRASS MALE FITTINGS AND HOSE GUARDS ON BOTH ENDS.

HEAVY DUTY TRUCK TIRE INFLATION KIT

WITH GLAD HAND AND DUAL FOOT AIR CHUCK PN 26050




Length: 50 ft. (15.24m), Male Fittings: 1/4" Brass, Max Pressure: 300 psi, Inside Diameter: 3/8" (9.2mm)

A simple way to top off your tires utilizing your on-board compressor!



GLAD HAND ATTACHES PAINLESSLY TO HEAVY-DUTY AIR BRAKE EQUIPPED TRUCKS



QUICK INFLATION WITH STRAIGHT-ON DUAL FOOT CHUCK

FOR USE WITH KEN-TOOL'S AIRBOSS AIR TOOLS AND OTHER BRANDS OF AIR TOOLS



Length: 2 ft. (61cm)
Max Pressure: 300 psi
1/4" SWIVEL MALE FITTING ON ONE END AND 1/4" FEMALE FITTING ON THE OTHER.

WHIP HOSE

SHORT LENGTH DESIGNED FOR CONNECTING ACCESSORIES PN 26024

www.KENTOOL.com

1-888-536-8665

768 E. North Street, P.O. Box 9320 | Akron, Ohio 44305 | Fax: 800-872-4929 | Phone: 330-535-7177 | Fax: 330-535-1345 | E-mail: sales@kentool.com

© 2020 Ken-Tool. All Rights Reserved. KT10082020