

HANDHELD AUTOMATIC TIRE INFLATOR PN 26012

- Digital display, audible warning, 2 presettable inflation settings.
- Auto Inflate and deflate with Over Pressure setting and underinflation protection
- Underinflation warning, will not auto inflate if tire pressure is less than 80% of the desired tire pressure.
- 12 foot hose with spring protector, Clip-on chuck & 8" dual foot chuck included
- 1/4" NPT thread for all air connection
- Accuracy +/- 0.3 psi @ 25-174 psi
- Batteries: DC 12V rechargeable Li-Ion battery
- Black Rubber cover
- Operating temperature: -14 to +122 degrees F (-10 to +50 C)
- Automatic shut off to save battery life



CHARGER VOLTAGE: INPUT AC
110 - 240 V (50-60 HZ)

PREMIUM DIGITAL TIRE INFLATOR PN 26081

Features a 24" hose, clip-on chuck and 8" dual foot chuck included.



CLEAR DIGITAL
READOUT
INCLUDING BATTERY
CHARGE STATUS

Both Ken-Tool Premium Digital Tire Inflators, 26081 & 26082, inflate, deflate and measure tire pressure. They have an accuracy of +/- 0.5 PSI across full range. Built with a solid metal alloy housing for extended service, all air connections have a 1/4" NPT thread. Max pressure is 175psi / 1,200 kPa / 12 Bar / 12 kgf, operating temperature between -4 to +140 degrees F (-20 to +60 C) and an automatic turn on and shut off feature to save battery life.

PREMIUM DIGITAL TIRE INFLATOR PN 26082

Features a 12' hose, clip-on chuck and 8" dual foot chuck included.

www.KENTOOL.com

1-888-536-8665

768 E. North Street, P.O. Box 9320 | Akron, Ohio 44305 | Fax: 800-872-4929 | Phone: 330-535-7177 | Fax: 330-535-1345 | E-mail: sales@kentool.com

© 2022 Ken-Tool. All Rights Reserved. KT05242022