



WHEREVER TIRES ARE CHANGED™

# JACK ROD

FLOOR JACK SUPPORT

- Fast and Easy Installation
- Compact tool that supports your floor jack in case of failure
- Creates a safe working environment to prevent serious injury or death



**SINGLE WHEEL JACK ROD**  
PN 21009

**JACK ROD**  
PN 21007

**JACK ROD XL**  
PN 21008

Item No.	Max Load	Compressed Length	Extended Length	Dimensions
21007	3 ½ Ton max load with the pin installed, 2 tons max load with out the pin	8"	14"	3½" Wide x 1½" Deep
21008	3 ½ Ton max load with the pin installed, 2 tons max load with out the pin	14"	24"	3½" Wide x 1½" Deep
21009	2 tons max load	8"	14"	3½" Wide x 2¼" Deep



USED WITH YOUR EXISTING FLOOR JACK FOR ADDITIONAL SUPPORT.



LOCKS YOUR JACK AT THE HEIGHT YOU NEED.



THE JACK ROD IS DESIGNED TO WORK WITH MOST FLOOR JACKS.



EXTENDS INTO PLACE WITH THE PUSH OF A LEVER.

[www.KENTOOL.com](http://www.KENTOOL.com)

**1-888-536-8665**

768 E. North Street, P.O. Box 9320 | Akron, Ohio 44305 | Fax: 800-872-4929 | Phone: 330-535-7177 | Fax: 330-535-1345 | E-mail: sales@kentool.com

© 2024 Ken-Tool. All Rights Reserved. KT01312024