Ken-Tool®

WHEREVER TIRES ARE CHANGED™

NINETEEN-FIVE™

PROUDLY MADE IN USA

MOUNTING/DEMOUNTING TOOL
PN 33199

TIRE MOUNTING & DEMOUNT TOOL SET FOR 19.5" TIRES
PN 33195

SPECIALLY DESIGNED TO WORK ON THE HUB SIDE TO MAKE YOUR JOB EASIER, FASTER AND SAFER!

New tire bar uniquely designed to work on hubside of wheel — where hub protrudes above rim. Specially designed ends manipulate tire with less effort. Tools are powder coated to protect from rust and corrosion. Forged from 3/4" diameter high-grade carbon steel and heat-treated for long-lasting strength and durability.

19.5" tires must be mounted and demounted with the wheel's Hub Side Up because the Drop Center of the wheel is closer to the hub! This makes changing the 19.5" tires notoriously difficult because the hub gets in the way of conventional bars and spoons. 19.5" tires are also stiffer with high ply ratings and thick beads. Patented Bead Holder to hold bead on 19.5" aluminum wheels.

Set Weight: 9.35 Lbs (4.25 kg)

Item No.	Description	Length	Weight	QTY
33199	Tire Mounting/Demounting Tool	38" (97 cm)	7 lbs (3.2 kg)	2
33196	**Patented** Bead Holder for 19.5" Aluminum Wheels	7-1/2" (19 cm)	1 lb (.5 kg)	1
31710	Bead Holder for Steel Wheels - Solid Brass	4-1/2" (11.5 cm)	1 lb (.5 kg)	1
31810	Aluminum Wheel Protector - Leather	6" (15 cm)	.35 lbs (.15 kg)	1

BENT END FOR MOUNTING AND DEMOUNTING BOTTOM BEAD

CURVED END FOR MOUNTING AND DEMOUNTING TOP BEAD

PART NO. 33196 BEAD HOLDER FOR 19.5" ALUMINUM WHEELS. PATENTED.

PART NO. 31710 BEAD HOLDER FOR STEEL WHEELS

PART NO. 31810 ALUMINUM WHEEL PROTECTOR. PATENTED.

YouTube

SEE MORE VIDEO DEMOS AT

Tire Bars For 19.5 Tires & Wheels

Nineteen-Five™ Tool Set: How To Use It On A 19.5 Wheel

www.KENTOOL.com

1-888-536-8665

768 E. North Street, P.O. Box 9320 | Akron, Ohio 44305 | 330-535-7177 | sales@kentool.com | © 2025 Ken-Tool. All Rights Reserved. KT20250131